


## The Ultraflat 79 floor drain DN 50, Des grating, Lock & Lift



### Article information

Item no.: 44700.63  
 GTIN: 4026092080917  
 Price group: 10

### Advantages

- Low installation depth
- Scientifically confirmed sound insulation effect
- different design covers

### Description

The Ultraflat 79 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

#### Variant

|                       |          |
|-----------------------|----------|
| System:               | 125      |
| SonicControl:         | optional |
| Sealing water height: | 50 mm    |

#### General characteristics

|                      |           |
|----------------------|-----------|
| Standard:            | EN 1253-1 |
| Nominal size (DN):   | 50        |
| Outer diameter (OD): | 50 mm     |

#### Dimensions

|                      |                                     |
|----------------------|-------------------------------------|
| Vertical adjustment: | 95 - 145 mm                         |
| Net weight:          | 0,88 kg                             |
| Gross weight:        | 0,93 kg                             |
| Vertical adjustment: | vertically adjustable upper section |
| Length:              | 227 mm                              |
| Width:               | 163 mm                              |
| Height:              | 79 mm                               |
| Packaging dimension: | length                              |
| Packaging dimension: | width                               |
| Packaging dimension: | height                              |

Tank/drain body  
Number of outlets: 1  
Material of drain body: ABS  
System: lateral

#### Coverage features

Type of cover: Design cover  
Cover material: Stainless steel 14301  
Colour of cover: silver  
Width of cover: 120 mm  
Height of cover: 16 mm  
Length of cover: 120 mm  
Surface: ground  
Frame material: Stainless steel 14301  
Cover locking: Lock & Lift  
Load class: L 15 (EN 1253-1)  
Grating colour: Kessel  
Slip resistance class: R9 according to DIN 51130; C according to DIN 51097

Rim length: 132 mm  
Rim material: 132 mm  
Shape of upper section: square  
Upper section material: ABS  
Odour trap: included